

Coach Lanterns



Description

This range of Polycarbonate, Cast Aluminium and Stainless Steel Lanterns are suitable for all environments, together with LED saving lamp range.

Features

- Available with LED lamps or without lamps
- Includes fixing screws and wall plugs
- 2-year guarantee (not including lamp)

PIR's

- PIR version incorporates photocell
- Adjustable time and lux levels on PIR
- Manual override facility on PIR

Stainless Steel Lanterns

- High grade brushed stainless steel – grade 304 – suitable for outdoor use

Technical Specification

Voltage	230V
Lampholder	E27
IP Rating	IP44
LED lamp	Megaman 9.5W 810lm 2800K colour temperature 4000K colour temperature 15,000 hours

PIR Specification

Detection range & Angle	8 meters @ 120°
Time range	10 sec – 7 minutes
Lux level range	2 – 1000 lux
Sensitivity range	1 meter – 8 meters
Manual override	Yes

Range

Polycarbonate Lanterns with LED Lamp

6 Panel PIR, 9.5W LED lamp	L2833BKLED#
6 Panel PIR, 9.5W LED lamp	L2833WHLED#
Half PIR, 9.5W LED lamp	L2835BKLED#
Half PIR, 9.5W LED lamp	L2835WHLED#

Polycarbonate Lanterns

6 Panel PIR	L2833BK
6 Panel PIR	L2833WH
Half Panel PIR	L2835BK
Half Panel PIR	L2835WH

Die-Cast Lanterns

6 Panel lantern	L2842W
6 Panel lantern	L2842B
6 Panel lantern PIR	L2843W
6 Panel lantern PIR	L2843B

Stainless Steel Lanterns

Lantern with PIR	L2863
Lantern with PIR, 9.5W LED lamp	L2863LED3

Where # is one of the following finishes:

- LED3 = Warm white lamp
- LED4 = Cool white lamp

Standards

- BS EN 60598-1
- BS EN 60598-2-1
- BS EN 55015
- BS EN 61547
- BS EN 61000-3-2
- BS EN 61000-3-3
- RoHS compliant